

STYLE REF: RF0007

STYLE NAME: MARBLE

Rock Fall[®]
INDUSTRY DEFINING SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S1P SRC | UK 6-12 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, MARBLE IS COMFORTABLE AND LIGHTWEIGHT, IT'S DEVELOPED WITH SPECIALIST COMFORT MATERIALS INCLUDING A SHOCK ABSORBING DUAL DENSITY PU NITRILE RUBBER OUTSOLE AND ACTIV-STEP[®] PU ANTI-FATIGUE COMFORT FOOTBED.

RF0007



activ[®]
step

Upper Material

Full grain black leather with breathable mesh panels

Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

Lining Materials

Moisture wicking breathable mesh fabric lining

Scuff Cap and Outsole

Shock absorbing dual density PU nitrile rubber outsole

Footbed

Activ-Step[®] PU anti-fatigue comfort footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/06/2019

WWW.ROCKFALL.COM | WWW.ROCKFALL.COM/PRODUCTS/MARBLE
PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited
Unit 1 Major House
Wimsey Way
Alfreton, Derbyshire
England. DE55 4LS

E: sales@rockfall.co.uk
T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Declares that the PPE described hereafter;

ROCK FALL MARBLE RF0007

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00331245** Issued by:-

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: Rock Fall UK Ltd Wimsey Way, Alfreton Trading Estate, Derbyshire, UK DE55 4LS	
Manufacturer	: [Redacted]	
Date of Issue	: 12 March 2013	
Expiry Date	: 25 January 2018	
Certificate No.	: LEC FI00331245 (Extension to certificate LEC FI00330577)	
Product Reference(s)	: RF007, TC130	
Description	: Construction	: Cemented
	: Toecap	: PEP# Composite
	: Midsole	: PEP# Composite
	: Last	: #PEP-PL
	: Sole	: PS-2050# MD + RB
	: Test Report(s)	: See Technical File
	: Size Range	: UK 6 – 13
	: Category	: S1P SRC

Assessor

12/03/2013

Date

Certification Manager

12/03/2013

Date

For and on behalf of **ITS Testing Services (UK) Limited**

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES



Number: GZHT90235625

Tests Conducted (As Requested By The Applicant)

2 Outsole Slip Resistance (EN ISO 20344:2004/A1:2007 (5.18), SRA, 23°C):

<u>Size</u>	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>		<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	Heel Part	0.48	Min. 0.28	Pass
	Flat Contact	0.53	Min. 0.32	Pass
<u>Size 42</u>	Heel Part	0.43	Min. 0.28	Pass
	Flat Contact	0.50	Min. 0.32	Pass
<u>Size 47</u>	Heel Part	0.50	Min. 0.28	Pass
	Flat Contact	0.51	Min. 0.32	Pass

3 Impact Resistance (Toe Protection) (EN ISO 20344:2004/A1:2007(5.4)):

<u>Size</u>			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	Left:	16.0 mm	Min. 13.5 mm (#)	Pass
	Right:	14.5 mm	Min. 13.5 mm (#)	Pass
<u>Size 42</u>	Left:	16.0 mm	Min. 14.0 mm (#)	Pass
	Right:	15.5 mm	Min. 14.0 mm (#)	Pass
<u>Size 47</u>	Left:	17.0 mm	Min. 15.0 mm (#)	Pass
	Right:	16.5 mm	Min. 15.0 mm (#)	Pass

Remark: # = In Addition, The Toecap Shall Not Develop Any Cracks On The Test Axis Which Go Through The Material, ie. Through Which Light Can Be Seen.

Expanded Uncertainty: 0.49(Urel), with k= 1.96 at 95% confidence level



Number: GZHT90238494

Tests Conducted (As Requested By The Applicant)

Outsole Slip Resistance (EN ISO 20344:2004/A1:2007 (5.18),SRB, 23°C):

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 40</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.14	Min. 0.13	Pass
	Flat Contact	0.18	Min. 0.18	Pass
<u>Size 42</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.14	Min. 0.13	Pass
	Flat Contact	0.19	Min. 0.18	Pass
<u>Size 47</u>	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.13	Min. 0.13	Pass
	Flat Contact	0.18	Min. 0.18	Pass